



Technical Drawing



Fields of Application



Standards of Application



Legend	
	/O
	/SR
	/TL

Exit Sign Recessed Wall Luminaires

Descriptions

+This energy efficient LED Exit Sign is supplied complete with SMD LED. Manufactured from a Lightweight Metal Frame and interchangeable PC Legends (Supplied as standard with Arrow Down. Optional Legends available at extra Cost). Product supplied can be used in a maintained or non maintained mode. Approx. Life 40,000 hrs.

Optical Specifications

- + The same lamp can be installed as a recessed, semi-recessed or surface fitting.
- + The lamp features a prismatic cover and is suitable both for ceiling and wall mounting.
- + Electronics prevents appliances from over-heating. Low working temperature maximises battery life.
- + Metal housing, powder coated RAL 9006. Any other RAL and NCS colours on request.
- + Luminous flux : about 60% of mains

Technical & Electrical Specifications

- + Mains voltage: 220V/50-60Hz ±10%
- + CE label and in conformity with EN standards. Lamp with individual battery
- + Battery: Maintenance-free Ni/Cd , 2h or 3h
- + Recharge time: 90% of capacity in 20 hours
- + Battery: Nickel cadmium 2.4V 4.8Ah
- + Charge Time: 24 hours recharging time

Options

- + Mounted : Recessed, surface wall and ceiling mounted
- + Lamps 1x T5 8W Fluorescent lamp 2.4V4500mAh Ni-Cd batteries pack
- + SMD 3W x 5W LED lamp 4.8V1800mAh Ni-Cd batteries pack

Product Details

Order Code	Lamp Type	Working Time	Dimensions (mm) a b c	Pcs/Pack
CST 100802	TLMini 8	2 hours	370x50x152	10
CST 100104	LED	2 hours	370x50x152	10
CST 100105	LED	3 hours	370x50x152	10